

NVR

Network video recorder

Integrate third-party cameras with your Ajax system in the smoothest way. NVR enables full camera synchronization with security devices, including binding intrusion events in the log to video archive timestamps and setting up a scenario to record by a detector alarm.





Secure cloud video management system



(8/16) CH 8 and 16-channel models



ONVIF/RTSP support





Essential capacities

- 8 or 16 channels with up to 4K resolution at a time.
- Up to 16 TB HDD support.
- NVR features a software motion detector that constantly analyses the image. Detection zone adjustment is available in the apps.
 Possible to switch between the NVR motion detector and the camera default.



Customizable video wall



Seamless connectivity

• NVR allows one to instantly jump from an event in the log to its video

Link specific devices alarms to recordings

recording in the archive.

- A dedicated video wall combining all the visual data in the system (including MotionCam detectors), available right from an Ajax app.
- NVR allows setting up a scenario where Ajax detectors trigger specific cameras to start recording. This results in fast and highresolution visual verification of alarms straight in mobile and desktop (monitoring) apps.

Technical Data Sheet: NVR

Smart user experience

- User-friendly interface for switching between streams and easy archive navigation. Quick archive response results in the smoothest timeline navigation you have ever experienced.
- NVR can work with cameras by identification in the DHCP network, so there is no need for additional settings in the same local network.
- Easy connection and setup through an encrypted Ajax Cloud server, both on-site and remotely. Check your cameras on the go in the



mobile app or easily organize a monitoring station with PRO Desktop.

Marked timeline for quick archive navigation

Privacy and security by design







access to video streams occurs through an Ajax account featuring passcodes/biometrics protection, two-factor authentication, and session control.



thanks to the Privacy menu, the trusted accounts can control users' access to specific streams and photos in real time.



Comprehensive archive protection:

all visual data is recorded on HDD by a unique pattern that can be read only by Ajax NVR. Physical HDD connection is tracked — the system logs an event on each connection or disconnection and sends a push notification through Ajax apps.



Installation under end-user control:

thanks to the temporary accesses for PRO accounts and the system administrator role, the end users can be assured that no backdoors or default passwords are left after the system is installed. Within an Ajax system, a video stream can only be accessed if a user has permission granted by the system administrator.

Power supply	110-240 V ~50/60 Hz	Compatibility	Hubs All Ajax hubs
	Consumption		
	up to 24 W		
Videostream	Channels	Installation	Operating temperature
	up to 8 or 16 cameras		range
			from 0°C to +40°C
	Resolution		
	up to 4K (25/30 fps)		Operating humidity

 $up (0 \mp 1 (20) 00 ip3)$

Decoding formats H.265/H.264

Bandwidth up to 100 Mbps

Capacity up to 16 TB disk storage HDD not included

HDD interface SATA connectivity, up to 75%

Protection class IP20



Technical Data Sheet: NVR

Enclosure NVR SmartBracket mounting panel Ethernet cable Installation kit Quick Start Guide

Colour white, black

> Weight 700 g

Tampering alarm





Complete set



ЛЛХ

Follow us to stay informed on upcoming releases.

f D (in



