## $\lambda J \lambda X$

Superior product line

## MotionCam S (PhOD) Jeweller

Wireless indoor motion detector supporting photo verification of alarms, Photo on Demand and Photo by Scenario functions.



## What's new

Baseline MotionCam (PhOD) Jeweller	Superior MotionCam (PhOD) S Jeweller	
SmartBracket mounting panel without holding screw	SmartBracket mounting panel with holding screw	
Common battery	Enhanced battery	
Available for all PROs	Available only for accredited partners	

This is the device of the Superior product line. Superior products are advanced versions of the Jeweller devices. This product line is developed for projects. Only accredited Ajax Systems partners can sell, install, and administer Superior products.



## Motion detection



1 – according to INCERT certification, detection range is up to 10 m



- SmartDetect algorithm to prevent false alarms
- Temperature compensation

Pet immunity



The detector has a built-in camera to request and view photos via Ajax apps. There are three types of photo verification: by alarm, by scenario, and on demand.

• Up to 640 × 480 pixels photo resolution

- Up to 5 photos in a series
- IR backlight for low light conditions



- Up to 1,200 m of radio communication in an open space
- Encryption and device authentication to prevent spoofing
- Regular polling to display current devices' status



- Up to 1,200 m of radio communication in an open space
- Unique uploading algorithm and data delivery confirmation
- Data backup and resending if the transmission is interrupted



- Up to 5 years of battery life
- Notifications on low battery
- Panasonic pre-installed battery



Pairing with a hub via QR code

- Remote control and configuration in the app
- Effortless installation and replacement

Intended certifications	Communication with control panel	Motion detection	Photo verification
EN 50131 (Grade 2)	Jeweller + Wings communication	Sensitive element	Photo resolution in pixels
PD 6662:2017 INCERT	technologies	1 × PIR sensor	640 × 480 320 × 240 (default)
NFA2P	Frequency bands	Detection distance	$160 \times 120$
SSF	868,0 - 868,6 MHz	up to 12 m <sup>1</sup>	Adjusted by PRO or user
			with admin rights in the Ajax app
Compatibility	Communication range	Detection angles	
Compatibility	up to 1,200 m	horizontal – 88.5°	Photos in a series
Hubs	In an open space	vertical – 80°	from 1 to 5 pics
Hub 2 (2G), Hub 2 (4G), Hub 2 Plus,			Adjusted by PRO or user
Hub Hybrid (2G), Hub Hybrid (4G)		Pet immunity	with admin rights in the Ajax app
		weight: up to 20 kg	
Range extenders		height: up to 50 cm	IR backlight
ReX 2			
Power supply	Installation	Enclosure	Complete set
Battery	Operating temperature range	Colour	MotionCam S (PhOD) Jeweller
1 × CR123A	from -10°C to +40°C	white, black	1 x CR123A (pre-installed)
Battery life	Operating humidity	Dimensions	SmartBracket with holding screw Installation kit
up to 5 years	up to 75%	110 × 65 × 50 mm	Quick start guide
Manufacturer	Protection class	Weight	
Panasonic	IP50	167 g	

1 – according to INCERT certification, detection range is up to 10 m



For detailed information, scan the QR code or follow the link:

ajax.systems/support/devices/motioncam-s-phod/



- @AjaxSystemsSupport\_Bot
- ajax.systems