

DS-KH6110-WE1 Network Indoor Station



The 4.3-inch series indoor station satisfies the demands of the entry level market and the intercom apartment market, which can provide flexible and convenient intercom functions, such as APP remote control, customized touch buttons functions, etc., while meeting the needs of customers with limited budgets.

- Easy and quick set-up: user friendly design
- 4.3-inch colorful touch screen with resolution of 480 × 272
- Standard PoE power supply without additional power adaptor
- Convenient Hik-Connect APP mobile control
- Views live videos of door stations and linked cameras
- Convenient for users to customize functions according to their own usage habits by 4 custom touch buttons

▪ Specification


System parameters	
Operating system	Linux
ROM	16 MB
RAM	128 MB
CPU	Embedded processor
Display parameters	
Screen size	4.3-inch
Operation method	Capacitive touch screen with 9 touch buttons
Type	Colorful TFT
Resolution	480 × 272
Video parameters	
Lens	/
Resolution	/
FOV	/
WDR	/
Video compression standard	/
Focal length	/
Audio parameters	
Audio compression standard	G.711 U, G.711 A
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Audio compression bitrate	64 Kbps
Audio quality	Noise suppression and echo cancellation
Volume adjustment	Adjustable
Capacity	
Event capacity	200
Notice capacity	200
Linked indoor extensions capacity	16
Network parameters	
Communication protocol	TCP/IP, SIP, RTSP
Wi-Fi standard	Wi-Fi 802.11 b/g/n, 2.4 GHz
Bluetooth version	/
3G/4G standard	/
Zigbee	/
Device interfaces	
Alarm input	/
Network interface	1 RJ-45 100 Mbps
TAMPER	/
RS-485	/
USB	/
TF card	/
Alarm output	/

General	
Button	9 touch buttons
Installation	Wall mounting, table mounting
Indicator	/
Weight	With package: 336.6 g (0.7 lbs) Without package: 197.8 g (0.4 lbs)
Protective level	/
Working temperature	-10 °C to 50 °C (14 °F to 122 °F)
Working humidity	10% to 90%
Dimensions	120 mm × 120 mm × 21 mm (4.7" × 4.7" × 0.83")
Application environment	Indoor
Power consumption	≤ 4 W
Language	English, French, Portuguese, Portuguese (Brazil), Spanish, Russian, German, Italian, Polish, Turkish, Vietnamese, Arabic, Czech, Hungarian, Dutch, Romanian, Bulgarian, Ukrainian, Croatian, Serbian, Greek, Lithuanian, Estonian, Latvian, Norwegian Danish, Slovenian, Slovak, Swedish, Finnish, Traditional Chinese, Mongolian, Hebrew, Kazakh, Uzbek
Power supply	IEEE802.3af, Standard PoE,12 VDC

▪ **Available Model**

DS-KH6110-WE1

▪ **Dimension**



Unit:mm [inch]

SCALE | 1:1

▪ **Accessory**

▪ **Optional**

DS-KABH6350-T
Table bracket



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

