



JI-113C Network camera outdoor 5Mpx - turret

Outdoor camera in turret design combines sharp images and compact design. Clear recordings in all weather conditions are always at your fingertips thanks to the MyJABLOTRON app.

Technical specifications

| Power supply | - from PoE (48V) data connection (according to IEE 802.3af) - alternatively via 12 V DC power connector |
|---------------------------------|---|
| Quiescent current consumption | 250 mA |
| Maximum current consumption | 458 mA |
| Number of pixels | 5 Mpix |
| Camera resolutions and bitrates | 1-5 MPx, 448-3072 kbps (according settings in app) |
| FPS | 15 |
| Lens | 3.6 mm (91° angle of view) |
| Lens type | M12 plate lens |
| Sensing chip | 1/2.7" Progressive CMOS |
| WDR - half-light compensation | yes |
| Camera setup options | horizontal: 91°, Vertical: 46° |
| Communication interface | LAN |
| IR illumination range | 30 m |
| Environment | outdoor general |
| Operating temperature range | -35 °C to +60 °C |
| Average operating humidity | up to 75 % non-condensing |
| Degree of protection | IP67 |
| Dimensions | ø 100 x 90 mm |



Camera weight 418 g

Weight of socket 317 g

In compliance with EN 55032, EN 50130-4, EN IEC 63000