

FOR314EDID Key Features:

- HDMI splitter function: distribute 1 HDMI source to 4 identical HDMI displays.
- HDMI2.0 and HDCP2.2 compliant.
- Supports Ultra HD 4Kx2K@60Hz.
- Supports EDID dip switch for switching HDMI output resolution and audio format.
- Supports HDR.
- Supports 3D.
- Metal heat sink design, work more stably.



Technical	
Input	HDMI ×1
Output	HDMI ×4
Input cable length	≤5m(AWG26 HDMI cable support HDMI2.0)
Output cable length	≤5m(AWG26 HDMI cable support HDMI2.0)
Video support	480i@60Hz、480p@60Hz、576i@50Hz、576p@50Hz、720p@50/60Hz、1080i@50/60Hz、1080p@50/60Hz、4K×2K@24/25/30/60Hz
HDR	Support
Audio format	Support standard audio and DSD (Direct Stream Digital) and HD(HBR) audio
TMDS signal	0.5 ~ 1.5Vp -p (TMDS)
DDC signal	5Vp-p (TTL)
EDID DIP Switch	YES
HDCP	HDCP2.2, HDCP1.4
Mechanical	
Housing	Iron
Dimensions(L×W×H mm)	158 × 80 × 17mm
Net weight	200g
Power supply	5V/1A
Power consumption	<3W
Operation temperature	0~60 °
Storage temperature	— 20~70 °
Relative humidity	20-90% (no condensation)