



19" 1.5U Rackmount 6-Output Power Distribution Unit (PDU)

EU CEE 7/3 Outlets, With On/Off Switch and Surge Protection, Built-in 3 m (10 ft.) Power Cord with EU CEE 7/4 Plug

Part No.: **713962**

EAN-13: 0766623713962 | UPC: 766623713962

Intellinet Network Solutions basic rack PDUs (Power Distribution Units) provide reliable power distribution via a single input with multiple output receptacles. Our current range is designed to distribute power from low amperage single phase electrical circuits.

Features:

- Outlets: 6
- Power input style: left-end single input
- Bracket installation style: frontal
- Cable plug: IEC60884
- Control functions: with switch
- Protection functions: surge protection
- Shell color & material: black aluminum
- Relative humidity: 10 - 90%
- Three-year warranty

Specifications:

- 1.5U Rackmount
- Socket/outlet standard: IEC60884
- Outlets: 6
- Cable specification: standard 3 m (10 ft.) power cord
- Cable type: H05VV-F 3G 1.5 mm²
- Size: 482.6 x 44.4 x 62 mm (L x W x H) / 19 (L) x 1.75 (W) x 2.44 (H) [in]
- Electrical rating: 250 V AC
- Maximum load current: 16 A
- Flammability: Tested and rated in accordance with UL 94 V-0

LED Indicators

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Green "SOURCE" LED
 - On: Surge protection is active and working properly
 - Off: Surge protection failed and is inactive
- Yellow "GND" LED
 - On: Unit is grounded properly with correct polarity
 - Off: Unit is grounded improperly, or L/N polarity is reversed
 - Blinking: Unit is grounded improperly, or electrical equipment is leaking
- Red "POWER" LED
 - On: Unit is receiving power
 - Off: Unit is not receiving power

