

SX-Series LCD Monitor 15" | 17" | 19"

A Secure Choice for Security

- Anti-Burn-in
- NeoV™ OPTICAL GLASS
- METAL CASING
- Black Level Alignment
- Gamma
- 24/7



Enhanced gamma selection, black-level alignment, and analogue image adjustment capabilities enable the SX-Series to display an upgraded level of surveillance images captured by conventional security cameras without any extra hassle. Crafted specifically for 24/7 security and surveillance duties, they are shielded with NeoV™ Optical Glass and metal casing, and AG Neovo's Anti-Burn-In™ technology guards them against ghosting.





Industry-leading Reliability

The SX-Series is specially designed to transcend the challenge of enduring 24/7 operations. AG Neovo's Anti-Burn-in™ technology also prevents image ghosting while performing nonstop mission-critical operations. Its metal casing and NeoV™ Optical Glass not only protect the SX-Series from damage but also keep maintenance easy.

Enhanced Gamma Selection


Selectable gamma curves visually optimise different kinds of images. The AG Neovo specialised image settings enhance colour, brightness, sharpness and contrast ratio, allowing the SX-Series to improve the light, shadows and colour balance of videos.



Others



AG Neovo SX-Series



Flexible Integration

The SX-Series is equipped with DisplayPort, HDMI, DVI, VGA, Composite and S-Video for digital and analogue signal support respectively.

Features

- LED-backlit technology with 1280 x 1024 / 1024 x 768 resolutions
- Crisp 20,000,000:1 dynamic contrast ratio
- Anti-Burn-in™ technology prevents image ghosting
- NeoV™ Optical Glass and metal housing for excellent cleanability and protection
- Image Enhancer: 3D Comb Filter / Deinterlace / Noise Reduction / Freeze
- Versatile connectivity: DisplayPort, HDMI, DVI, VGA, Component/ Composite, S-Video
- Alink™ function for synchronized powering on/off via HDMI
- BNC passive loop-through output port
- RS232 control support - provides compatibility with control systems
- Front-sided IP22 Compliant (IEC 60529 Standard) (19" and 17" only)
- EcoSmart Sensor automatically adjusts brightness level according to ambient lighting conditions
- Flicker-free display technology reduces eye discomfort
- Quick signal-switching time (≤ 0.8 sec.)
- Gamma selection and black-level adjustment
- Selectable aspect ratio
- Built-in speakers
- Designed and developed for continuous 24/7 operation
- Premium-grade panel for high reliability and long product lifetime
- VESA mount compatibility for flexible installation

| Specifications | SX-15E | SX-17E | SX-19E |
|--------------------------------|---|---|---|
| Panel | | | |
| Panel Type | LED-Backlit TFT LCD (VA Technology) | LED-Backlit TFT LCD (TN Technology) | LED-Backlit TFT LCD (TN Technology) |
| Panel Size | 15.0" | 17.0" | 19.0" |
| Max. Resolution | XGA 1024 x 768 | SXGA 1280 x 1024 | SXGA 1280 x 1024 |
| Pixel Pitch | 0.297 mm | 0.264 mm | 0.294 mm |
| Brightness | 300 cd/m ² | 250 cd/m ² | 250 cd/m ² |
| Contrast Ratio | 20,000,000:1 (DCR) | 20,000,000:1 (DCR) | 20,000,000:1 (DCR) |
| Viewing Angle (H/V) | 176°/176° | 170°/160° | 170°/160° |
| Display Colour | 16.2M | 16.7M | 16.7M |
| Response Time | 5 ms | 3 ms | 3 ms |
| Frequency | | | |
| Frequency (H) | 24 kHz-81 kHz | 24 kHz-81 kHz | 24 kHz-81 kHz |
| Frequency (V) | 50 Hz-75 Hz | 50 Hz-75 Hz | 50 Hz-75 Hz |
| Signal Input | | | |
| DisplayPort | x 1 | x 1 | x 1 |
| HDMI | 1.4 x 1 | 1.4 x 1 | 1.4 x 1 |
| DVI | 24-Pin DVI-D | 24-Pin DVI-D | 24-Pin DVI-D |
| VGA | 15-Pin D-Sub x 1 | 15-Pin D-Sub x 1 | 15-Pin D-Sub x 1 |
| Composite | BNC x 2 | BNC x 2 | BNC x 2 |
| S-Video | 4-Pin mini DIN x 1 | 4-Pin mini DIN x 1 | 4-Pin mini DIN x 1 |
| Signal Output | | | |
| Composite | BNC x 2 | BNC x 2 | BNC x 2 |
| External Control | | | |
| RS232 In | 2.5 mm Phone Jack | 2.5 mm Phone Jack | 2.5 mm Phone Jack |
| Other Connectivity | | | |
| USB | 2.0 x 1 (Service Port) | 2.0 x 1 (Service Port) | 2.0 x 1 (Service Port) |
| Audio | | | |
| Audio In | Stereo Audio Jack (3.5 mm), Stereo Audio Jack (RCA) | Stereo Audio Jack (3.5 mm), Stereo Audio Jack (RCA) | Stereo Audio Jack (3.5 mm), Stereo Audio Jack (RCA) |
| Audio Out | Stereo Audio Jack (RCA) | Stereo Audio Jack (RCA) | Stereo Audio Jack (RCA) |
| Internal Speakers | 2W x 2 | 2W x 2 | 2W x 2 |
| Power | | | |
| Power Supply | External | External | External |
| Power Requirements | DC 12V, 1.42A | DC 12V, 1.58A | DC 12V, 1.67A |
| On Mode | 11W (On) | 12W (On) | 13W (On) |
| Stand-by Mode | < 0.5W | < 0.5W | < 0.5W |
| Off Mode | < 0.5W | < 0.5W | < 0.5W |
| Glass | | | |
| Thickness | 3.0 mm (0.12") | 3.0 mm (0.12") | 3.0 mm (0.12") |
| Reflection Rate | < 1% | < 1% | < 1% |
| Transmission Rate | > 97% | > 97% | > 97% |
| Hardness | > 9H | > 9H | > 9H |
| Operating Conditions | | | |
| Temperature | 0°C-40°C (32°F-104°F) | 0°C-40°C (32°F-104°F) | 0°C-40°C (32°F-104°F) |
| Humidity | 10%-90% (non-condensing) | 10%-90% (non-condensing) | 10%-90% (non-condensing) |
| Storage Conditions | | | |
| Temperature | -20°C-60°C (-4°F-140°F) | -20°C-60°C (-4°F-140°F) | -20°C-60°C (-4°F-140°F) |
| Humidity | 5%-95% (non-condensing) | 5%-95% (non-condensing) | 5%-95% (non-condensing) |
| Mounting | | | |
| VESA FPMPI | Yes (100 x 100 mm & 75 x 75 mm) | Yes (100 x 100 mm & 75 x 75 mm) | Yes (100 x 100 mm & 75 x 75 mm) |
| Stand | | | |
| Tilt | 0° to 20° | 0° to 20° | 0° to 20° |
| Security | | | |
| Kensington Security Slot | Yes | Yes | Yes |
| Dimensions | | | |
| Product with Base (W x H x D) | 380.0 x 359.0 x 155.0 mm (15.0" x 14.1" x 6.1") | 409.4 x 398.2 x 175.0 mm (16.1" x 15.7" x 6.9") | 445.4 x 420.2 x 175.0 mm (17.5" x 16.5" x 6.9") |
| Product w/o Base (W x H x D) | 380.0 x 315.0 x 53.5 mm (15.0" x 14.1" x 2.1") | 409.4 x 361.9 x 64.5 mm (16.1" x 15.7" x 2.5") | 445.4 x 383.9 x 64.5 mm (17.5" x 15.1" x 2.5") |
| Packaging (W x H x D) | 475.0 x 460.0 x 204.0 mm (18.7" x 18.1" x 8.0") | 510.0 x 493.0 x 224.0 mm (20.0" x 19.4" x 8.8") | 535.0 x 512.0 x 225.0 mm (21.1" x 20.2" x 8.9") |
| Weight | | | |
| Product w/o Base | 4.3 kg (9.5 lb) | 5.3 kg (11.7 lb) | 6.2 kg (13.7 lb) |
| Product with Base | 4.7 kg (10.4 lb) | 6.1 kg (13.4 lb) | 7.0 kg (15.4 lb) |
| Packaging | 6.7 kg (14.8 lb) | 7.8 kg (17.2 lb) | 8.7 kg (19.2 lb) |
| Regulation Approval | | | |
| Certifications & Compliance | FCC, CE, CB, BSMI, WEEE, RoHS, REACH, EAC | FCC, CE, CB, BSMI, WEEE, RoHS, REACH, EAC | CB, CE, FCC, BSMI, RoHS, WEEE, REACH, EAC |
| Accessories | | | |
| Supplied | Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card | Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card | Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card |
| Optional Accessories | | | |
| Ceiling Mount (Landscape only) | CMP-01+WMK-03 | CMP-01+WMK-03 | CMP-01+WMK-03 |
| Wall Mount (Landscape only) | WMA-01, WMK-01, WMK-03, PMK-01 | WMA-01, WMK-01, WMK-03, PMK-01 | WMA-01, WMK-01, WMK-03, PMK-01 |
| Desk Mount (Landscape only) | DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02 | DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02 | DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02 |

Global Headquarters

Taipei, Taiwan

EMEA Regional Headquarters

Capelle a/d IJssel, The Netherlands

North & South America Regional Headquarters

San Jose, CA, U.S.A.

Asia-Pacific Regional Headquarters

Taipei, Taiwan

Canada Sales Office

Vancouver, B.C., Canada

China Sales Office

Shanghai, China

Czech Republic Sales Office

Brno, Czech Republic

Denmark Sales Office

Støvring, Denmark

Germany Sales Office

Mechernich, Germany

Italy Sales Office

Livorno, Italy

Poland Sales Office

Warsaw, Poland

Spain Sales Office

Barcelona, Spain

Ukraine Sales Office

Lviv, Ukraine

displays.agneovo.com